

CERTIFICATE

TÜV NORD CERT GmbH
herewith declares that

ZheJiang GangHang Solar Technology Co., Ltd.
No.2, West Xintiandi Business Centre, Xiacheng Zone
Hangzhou City, Zhejiang Province, 310006
P.R. China

is authorized to provide the product mentioned below with the mark as illustrated:

Description of product (details see Annex 2):

PV Modules with 6" Mono-crystalline Silicon Solar Cells

PV Modules with 6" Half-cut Mono-crystalline Silicon Solar Cells



Valid from: 2019-12-04

Valid until: 2024-06-13

Tested according to: IEC / EN 61215-1:2016;
IEC / EN 61215-1-1:2016;
IEC 61215-2:2016 / EN 61215-2:2017 + AC:2017 + AC:2018;
IEC 61730-1:2016 / EN IEC 61730-1:2018 + AC:2018;
IEC 61730-2:2016 / EN IEC 61730-2:2018 + AC:2018.

Registered No.: 44 780 19 406749 - 388

Manufacturer: see Annex 1

Test Report No.: 492011334.001

File No.: SHV10063/19



TÜV NORD CERT GmbH
Certification Body
Consumer Products



Essen, 2019-12-04

Please also pay attention to the information stated overleaf.

Anlage 1 zum Zertifikat Nr.: / Annex 1 to Certificate No.: 44 780 19 406749 - 388

Seite / Page 1 von / of 1

Aktenzeichen: / File reference: SHV10063/19

2019-12-04

Manufacturer:

Manufacturer: Maysun Solar Co., Ltd
Factory inspection report no.: 862010444.001

Remark:

Factory inspection is mandatory to be performed annually. Please refer to factory inspection report for detailed information.

A handwritten signature in blue ink, appearing to read "R. R. R. R. R." or similar, written in a cursive style.

TÜV NORD CERT GmbH
Certification Body
Consumer Products

Description of product(s):

Module types:	PV Modules with 6" Mono-crystalline Silicon Solar Cells: 72 cells: MSxxxM-72 (xxx = 325W-390W, in increment of 5) 60 cells: MSxxxM-60 (xxx = 275W-325W, in increment of 5)
Maximum system voltage:	1500V
Fuse rating:	16A
Electrical protection class:	Class II
Pollution degree:	1
Material group:	I
Design load (positive / negative):	3600Pa / 1600Pa
Safety factors:	1.5
Fire safety class:	Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018)

Module types:	PV Modules with 6" Half-cut Mono-crystalline Silicon Solar Cells: 144 cells: MSxxxM-72H (xxx = 350W-390W, in increment of 5) 120 cells: MSxxxM-60H (xxx = 290W-325W, in increment of 5) 144 cells: MSxxxMB-72H (xxx = 385W-410W, in increment of 5) 120 cells: MSxxxMB-60H (xxx = 320W-340W, in increment of 5)
Maximum system voltage:	1500V
Fuse rating:	20A
Electrical protection class:	Class II
Pollution degree:	1
Material group:	I
Design load (positive / negative):	3600Pa / 1600Pa
Safety factors:	1.5
Fire safety class:	Class C according to ANSI/UL 1703-2018 (as per ANSI/UL 790-2018)

Remark:

For detailed product information, please refer to CDF (Constructional Data Form) in Annex 1 of test report.



TÜV NORD CERT GmbH
Certification Body
Consumer Products